


INVENGO XC-RF855 DESKTOP READER



About Invengo's XC-RF855 Desktop Reader

Invengo's XC-RF855 Desktop RAIN RFID reader is a comprehensive (UHF) reading and writing station equipped with an integrated RFID reader module and built-in antenna. The device has excellent read and write performance, suitable within a variety of applications like retail, health care, and many others.



Invengo – the global RFID technology provider – is a leading developer and manufacturer of high quality, intelligent RAIN RFID and HF/NFC connectivity solutions and consumables (tags & inlays) utilized in the Internet of Things. With a focus on RFID innovation, Invengo has created a leading product line in retail, (industrial) laundry, library, (public) transportation, healthcare, and many other industries.

Invengo Technology Pte. Ltd. (SG) is the International Headquarters of Invengo Information Technology Co. Ltd, listed on Shenzhen Stock Exchange (SZSE: 002161.SZ). Employing over 600 people globally, Invengo is one of the largest publicly traded, RFID / IoT oriented companies in the world.

Features

- Slim and robust designed Desktop Reader
- Comprehensive SDK for software development
- Expandable functionalities
- Standard USB interface
- UX friendly software
- Easy to deploy

All features and specifications described are subject to change without notice.

Product Specifications

Physical Parameters

Dimensions	345 x 270 x 25,5 mm (13.6 x 10.6 x 1 in)
Weight	2,5 kg (5.5 Lbs)
Case Material	Aluminum Alloy, Tampered Glass

Environmental

Operating Temperature	-10°C to 55°C (14°F to 131°F)
Storage Temperature	-15°C to 60°C (5°F to 140°F)
Humidity Range	5% to 95%, non-condensing

Power Source

Adapter (not included)	AC input 100V-240V,50 - 60 Hz; DC / output 4,5 ~6V/4A Supply current \geq 2A Supply jitter <100mV
-------------------------------	--

Communication/Network

Host Interface	USB
Indicators	Power indicator, LED indicator and Buzzer

UHF RFID

Supported Protocols	EPC global UHF Class 1Gen2, ISO/IEC 18000-63
Frequency	920 to 925 MHz

Performance Parameter

Read Range	0 to 3 m (adjustable by power settings)
Multiple Tag Reading	Up to 20 tags
RF Boundary	< 20 cm
RF Output Power	0 to 27 dBm, configurable in 1 dBm steps

APAC

Invengo Technology Pte. Ltd
10 Kallang Avenue
#05-15 Tower 2, Aperia
Singapore 339510

Office: +65 6702 3909
sales.apac@invengo.com

Americas

Invengo Technology Corp.
2700-160 Sumner Blvd.
Raleigh, NC 27616
United States of America

Office: +1 919 890 0202
sales.americas@invengo.com

EMEA

Invengo Technologies
180 Voie Ariane – Athélia 1
13600 La Ciotat
France

Office: +33 413 96 1111
sales.emea@invengo.com